




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 10/00, 17/00	A2	(11) International Publication Number: WO 00/12009 (43) International Publication Date: 9 March 2000 (09.03.00)
<p>(21) International Application Number: PCT/US99/19123</p> <p>(22) International Filing Date: 24 August 1999 (24.08.99)</p> <p>(30) Priority Data: 09/146,185 1 September 1998 (01.09.98) US</p> <p>(71) Applicant: SENORX, INC. [US/US]; Suite 144, 13766 Alton Parkway, Irvine, CA 92618 (US).</p> <p>(72) Inventors: BURBANK, Fred, H.; 30982 Steeplechase Drive, San Juan Capistrano, CA 92675 (US). LUBOCK, Paul; 30 Bethany, Laguna Niguel, CA 92677 (US). JONES, Michael, L.; 34441 Camino el Molino, Capistrano Beach, CA 92624 (US). QUICK, Richard, L.; 32181 Fall River Road, Trabuco Canyon, CA 92679 (US).</p> <p>(74) Agent: STOUT, Donald, E.; Stout, Uxa, Buyan & Mullins, LLP, 4 Venture #300, Irvine, CA 92618 (US).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>	

(54) Title: SECURING SURGICAL INSTRUMENTS AT TARGET TISSUE SITES



(57) Abstract

Devices and methods are provided for securely affixing a medical instrument to desired tissue in a patient's body, using a fixation agent. Such medical instruments may comprise localization wires or tissue acquisition instruments, such as biopsy instruments, for example. In the case of tissue acquisition instruments, the inventors have discovered significant advantages for securely affixing the distal end of the tissue acquisition instrument to a particular tissue target area. For example, such an approach permits the imaging environment to be uncoupled from the procedural environment so that expensive and often unavailable imaging equipment, such as stereotactic imaging equipment, need not be used. In a preferred embodiment, a bonding agent, such as adhesive, surgical glue, or a solvent, is used as the fixation agent.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SECURING SURGICAL INSTRUMENTS AT TARGET TISSUE SITES

Field of the Invention

The present invention relates to methods and devices for ensuring that a medical instrument remains in a desired location within a patient's body during a medical procedure, and more particularly to methods and devices for affixing a distal end of the medical instrument to the desired location using adhesives.

Background of the Invention

It is often desirable and frequently necessary to sample or remove a portion of tissue from humans and other animals, particularly in the diagnosis and treatment of patients with cancerous tumors, pre-malignant conditions, and other diseases or disorders.

5 Typically, in the case of cancer, particularly cancer of the breast, there is a great emphasis on early detection and diagnosis through the use of screening modalities, such as physical examination, and particularly mammography, which is capable of detecting very small abnormalities, often nonpalpable. When the physician establishes by means of a mammogram or other screening modality,
10 such as ultrasound, that suspicious circumstances exist, a biopsy must be performed to capture tissue for a definitive diagnosis as to whether the suspicious lesion is cancerous. Biopsy may be done by an open or percutaneous technique. Open biopsy is a surgical procedure using a scalpel and involving direct vision of the target area, for removing the entire mass (excisional biopsy) or a part of the
15 mass (incisional biopsy). Percutaneous biopsy, on the other hand, is usually done with a needle-like instrument through a relatively small incision, blindly or with the aid of an artificial imaging device, and may be either a fine needle aspiration

(FNA) or a core biopsy. In FNA biopsy, individual cells or clusters of cells are obtained for cytologic examination and may be prepared such as in a Papanicolaou smear. In core biopsy, as the term suggests, a core or fragment of tissue is obtained for histologic examination which may be done via a frozen
5 section or paraffin section.

The type of biopsy utilized depends in large part on circumstances present with respect to the patient, including the location of the lesion(s) within the body, and no single procedure is ideal for all cases. However, core biopsy is extremely useful in a number of conditions and is being used more frequently by the
10 medical profession.

When an open surgical biopsy procedure is indicated, current practice dictates the use of lesion localization needles and devices, commonly referred to as "localization wires", for use in localizing or marking non-palpable lesions and tumors within the body. These devices generally comprise a hypodermic needle
15 or cannula which is inserted into the body under local anesthesia to the lesion or tissue of interest. The wire marker, or localization wire, is then passed through the cannula and extends through the lesion of interest so that the distal end thereof is anchored beyond the lesion. Thus, the lesion is marked for subsequent surgical procedures such as excision or biopsy. The anchoring procedure is
20 typically accomplished by means of mechanical structure disposed at the distal end of the wire marker, such as a barb, hook, or the like, which is attached to surrounding tissue. After marking the lesion with the wire marker, the cannula is usually removed from the body, leaving the wire in place and extending from the body, for subsequent use by the surgeon during the biopsy procedure in
25 identifying the lesion location. However, it often occurs that the barb or hook at the distal end of the wire marker attaches to something other than the tumor or lesion. For example, in the case of breast biopsies, the breast will typically be placed in compression during the imaging procedure in order to properly identify the location of the target lesion and place the localization wire. However, breast
30 tissue is comprised of fibrous bands which, in compression, may be close to the

target lesion and inadvertently engaged by the barb of the localization wire.

Later, when the breast is released from compression prior to the surgical procedure, the fibrous bands will move away from the target lesion, and the distal end of the localization wire may thus move a substantial distance away from the target lesion.

It would be desirable, therefore, to develop a localization wire system and method wherein the distal end of the localization wire could be positively attached to the target lesion in order to minimize the possibility of migration of the distal end of the localization wire away from the target lesion between the imaging and surgical procedures.

In circumstances where a core biopsy procedure is indicated, various systems are available. Such systems are shown, for example, in U.S. Patent No. 5,526,822 to Burbank et al, which discloses a probe having a laterally disposed tissue receiving port at the distal end thereof for acquiring relatively small tissue samples, and in U.S. Patent No. 5,111,828 to Kornberg et al., which discloses a probe having an axially disposed tissue receiving port at the distal end thereof for acquiring relatively large intact tissue samples. Both of these patents are expressly incorporated by reference herein.

U.S. Application Serial No. 09/057,303 to Burbank et al., commonly assigned with the present application and expressly incorporated by reference herein, discloses still another core biopsy apparatus, which advantageously permits the acquisition of tissue samples which are larger in diameter than the diameter of the instrument lumen, thereby greatly increasing the chances of completely removing the target lesion and leaving "clean" margins thereabout.

As in the case of localization wires, there is some risk in using any of the foregoing devices that the distal end of the instrument will migrate away from the target lesion during the biopsy procedure, thereby reducing the likelihood of removing target tissue. Heretofore, in the case of core biopsy procedures, the risk of this occurrence is minimized by employing image guidance techniques during the entire tissue removal procedure. For example, in the case of the '822

Burbank et al. patent, a stereotactic imaging guidance system is typically utilized during the disclosed procedure. One disadvantage of this approach, however, is that the patient's breast must remain in compression during the entire procedure, with attendant discomfort and increased procedural difficulty, in order to properly
5 utilize the imaging equipment. Furthermore, stereotactic imaging equipment or other suitable alternatives can cost as much as \$400,000 or more and is not in the usual inventory of a typical community hospital. It would therefore be quite advantageous if a method and apparatus could be developed which would permit the uncoupling of the imaging environment from the procedural environment
10 without undue risk that the active or cutting end of the core biopsy instrument would migrate away from the target lesion during the interval between the imaging procedure and the biopsy procedure.

Summary of the Invention

15 The present invention solves the problems outlined above by describing devices and methods for securely affixing a localization wire to desired tissue in a patient's body, so that after the patient is moved from the imaging environment to the procedural environment, the practitioner will have assurance that the
20 localization wire is still accurately placed. Additionally, devices and methods are described for ensuring that the distal end of a tissue acquisition instrument, such as a biopsy instrument, is securely affixed to a particular target area, such as a lesion, in a patient's body, thereby advantageously permitting the imaging environment to be uncoupled from the procedural environment so that expensive
25 and often unavailable imaging equipment, such as stereotactic imaging equipment, need not be used.

More particularly, in one aspect of the invention a medical device is provided comprising a tube having a distal end, a proximal end, and a longitudinal axis, wherein the device is adapted for placement of the distal end
30 thereof into a patient's body at a desired location. The medical device includes a

fixation agent, which may comprise any one of a bonding agent, a mechanical fixation agent, or an electrosurgical coagulation element, disposed on the distal end thereof, which is adapted for affixing the distal end of the medical device at the desired location.

5 The medical device may comprise, for example, a localization wire for use in connection with an open biopsy procedure. Alternatively, the device may comprise a tissue acquisition instrument, such as a biopsy instrument. In the preferred embodiment, the fixation agent is a bonding agent, comprising a surgical adhesive, glue, or solvent.

10 In another aspect of the invention, a tissue acquisition instrument is provided for retrieving body tissue, having a longitudinal axis and which comprises a distal end adapted for entry into a patient's body, a cutting element disposed on the instrument for cutting surrounding tissue, and structure disposed on the distal end for securing the tissue acquisition instrument at a predetermined
15 desired location, in order to ensure that the tissue acquisition instrument remains in place during a tissue acquisition procedure so that desired tissue is properly acquired.

 In yet another aspect of the invention, a method of performing a medical procedure is provided, using a medical device comprising a tube having a distal
20 end, a proximal end, and a longitudinal axis. The method first comprises the step of placing the distal end of the tube in a patient's body, so that the distal end is disposed in a desired tissue location. Then, a bonding agent is dispensed for the tube into tissue surrounding the distal end, so that the distal end of the tube becomes affixed to the desired tissue location.

25 In still another aspect of the invention, a method is provided for performing a tissue acquisition procedure using a tissue acquisition instrument having a distal end, a proximal end, a longitudinal axis, and a cutting element. In this method, the distal end of the instrument is placed into a patient's body, so that the distal end is disposed in a desired tissue location. Then, the distal end of
30 the instrument is affixed to the desired tissue location, so that the instrument does

not move relative to the desired tissue location during the tissue acquisition procedure. The cutting element is then actuated to acquire one or more tissue samples.

5 The invention, together with additional features and advantages thereof, may best be understood by reference to the following description taken in conjunction with the accompanying illustrative drawing.

Brief Description of the Drawing

10 Fig. 1 is a schematic plan view of a first embodiment of the present invention, illustrating a catheter for a localization wire introduction and infusion system wherein an introducer needle for introducing the localization wire into a patient's body remains in place during securement of the localization wire to surrounding tissue using a bonding agent;

15 Fig. 2 is a schematic plan view of the introducer needle used in conjunction with the catheter of Fig. 1;

20 Fig. 3 is a schematic plan view of one embodiment of a localization wire which may be used in conjunction with the infusion system shown in Figs. 1 and 2;

25 Fig. 3a is a perspective view of the distal end of the embodiment shown in Figs. 1-3, wherein the introducer needle is inserted through the lumen of the catheter;

30 Fig. 3b is a perspective view of the distal end of the embodiment shown in Figs. 1-3, wherein the introducer needle is inserted through the lumen of the catheter, and its position within the catheter lumen is shown in phantom for illustrative purposes;

Fig. 3c is a perspective view similar to Fig. 3a, wherein the localization wire is inserted through the lumen of the catheter;

5 Fig. 4 is a perspective view of a second embodiment of the present invention, illustrating a second embodiment of a localization wire introduction and infusion system, wherein an introducer needle for introducing the localization wire into a patient's body is removed during securement of the localization wire to surrounding tissue using a bonding agent;

10 Fig. 5 is schematic plan view of the catheter for the system illustrated in Fig. 4;

Fig. 6 is a schematic plan view of the introducer needle for the system illustrated in Figs. 4 and 5;

15 Fig. 6a is a perspective view of the distal end of the embodiment shown in Figs. 4-6, wherein the localization wire is inserted through a lumen of the catheter;

20 Fig. 7 is a schematic plan view of a second embodiment of a localization wire which may be utilized in conjunction with either of the embodiments of Figs. 1-3 or 4-6;

25 Fig. 8 is a schematic view in isolation illustrating one embodiment of the present invention for storing and releasing a bonding agent which is dispensed from a medical instrument for affixing the medical instrument to surrounding tissue in a patient's body;

30 Fig. 9 is a perspective view of a third embodiment of the present invention, illustrating a catheter which may be used as a localization wire and

infusion system;

Fig. 10 is an enlarged perspective view of the distal end of the cannula illustrated in Fig. 9, showing in greater detail the perforations in the distal end for
5 infusing a bonding agent to surrounding tissue;

Fig. 11 is a perspective view of a modified version of the embodiment shown in Figs. 9 and 10, wherein the cannula is comprised of a braided polymer tubing and the interstices between the braids function as the infusion openings for
10 infusing bonding agent to surrounding tissue;

Fig. 12 is a perspective view of another modified version of the embodiment shown in Figs. 9 and 10, wherein the cannula is comprised of a coil and the interstices between expanded coils function as the infusion openings for
15 infusing bonding agent to surrounding tissue;

Fig. 13 is a perspective view of a biopsy instrument constructed in accordance with the principles of the present invention;

20 Fig. 14 is a perspective view of a second modified embodiment of a biopsy instrument having an expandable Mallicot structure at its distal end for anchoring the instrument at a particular tissue site;

Fig. 15 is a perspective view of a third modified embodiment of a biopsy
25 instrument having a modified expandable Mallicot structure at its distal end for anchoring the instrument at a particular tissue site;

Fig. 16 is a perspective view of a fourth modified embodiment of a biopsy instrument having an expandable linkage structure at its distal end for anchoring
30 the instrument at a particular tissue site, wherein the linkage structure is shown in

its retracted position;

Fig. 17 is a perspective view of the embodiment shown in Fig. 16,
wherein the linkage structure is shown in its expanded position;

5

Fig. 18 is a perspective view of a fourth modified embodiment of a biopsy
instrument having an extendable "bottle brush" structure at its distal end for
anchoring the instrument at a particular tissue site;

10 Fig. 19 is a perspective view of a fifth modified embodiment of a biopsy
instrument having a nitinol flap structure at its distal end, expandable upon
retraction of a surrounding sleeve, for anchoring the instrument at a particular
tissue site;

15 Fig. 20 is a perspective view of a sixth modified embodiment of a biopsy
instrument having a rolled stent structure at its distal end which unrolls upon
retraction of a surrounding sleeve, for anchoring the instrument at a particular
tissue site;

20 Fig. 21 is a perspective view of a seventh modified embodiment of a
biopsy instrument having expandable spiral wires at its distal end for anchoring
the instrument at a particular tissue site; and

25 Fig. 22 is a perspective view of an eighth modified embodiment of a
biopsy instrument having an expandable basket at its distal end for anchoring the
instrument at a particular tissue site.

Detailed Description of the Invention

30 Referring now more particularly to the drawings, Figs. 1-3c illustrate a

first embodiment of the invention, wherein a medical instrument 10 (Figs. 3a-3c) comprises a catheter 12 (Figs. 1, 3a-3c), an introducer needle 14 (Figs. 2, 3a, and 3b), and a localization wire 16 (Figs. 3, 3c). In this embodiment, which may be styled as a "needle in" infusion system, the introducer needle 14 comprises a sharp distal end 18, which is inserted through an entry hole 20 in the catheter 12 (Fig. 1), so that its tip 18 extends beyond the distal end 22 of the catheter 12, as shown in Figs. 3a and 3b. The introducer needle 14 may include a stop 24 having an enlarged diameter, which is adapted to engage the distally tapering inner sidewall of the catheter 12 at a predetermined point, as generally shown particularly in Fig. 3b, to ensure that the tip 18 properly extends beyond the distal end 22 of the catheter 12. The introducer needle 14 and catheter 12 together are then introduced into a patient's body (not shown), using known imaging techniques for guiding localization wires to the site of tissue to be excised ("target tissue").

Once the catheter 12 and introducer needle 14 are in position relative to the target tissue, the introducer needle 14 is removed proximally from the catheter 12, and the localization wire 16 is inserted distally through the entry hole 20 and pushed distally through the lumen in the catheter 12, so that the distal end of the localization wire 16 extends distally of the distal end of the introducer needle and catheter, as shown in Fig. 3b. Indicator marks 25 preferably assist the practitioner in ensuring that the localization wire is properly inserted to the required depth.

Localization wires such as the wire 16 typically include some type of mechanical anchoring means, such as a barb or hook 26, for securing the distal end of the localization wire 16 in position behind the target tissue. However, this approach is often inadequate, as discussed supra in the Background portion of the specification, because the tissue to which the hook 26 becomes attached will often shift relative to the target tissue between the imaging step of the medical procedure, which is usually a biopsy, such as a breast biopsy, and the ensuing surgical step, which usually takes place in a different area of the hospital and

requires transportation and resultant jostling of the patient from the radiology department to the operating room. The present invention, therefore, contemplates an advantageous additional step of employing a bonding agent, which may comprise any known material which is capable of creating a bond between the distal end of the medical instrument 10 and surrounding tissue. Once the localization wire is properly placed at the desired target tissue site, under imaging guidance, the bonding agent is dispensed from the distal end of the medical instrument to the surrounding tissue to create the desired bond. In the embodiment of Figs. 1-3a, a plurality of infusion ports 28 are disposed along the length of the distal end of the catheter 12. Any number of infusion ports (one or more) may be employed in order to optimize the flow of bonding agent to the tissue, and they are preferably staggered circumferentially about the catheter in order to evenly deliver bonding agent about the circumference of the instrument 10. Various delivery means may be employed as well. For example, in the illustrated embodiment, the catheter 12 comprises a proximal hub 30 (Fig. 1), including a stopcock 32 which is engageable with a syringe (not shown) containing the bonding agent. When the localization wire is properly positioned, the practitioner injects the bonding agent into the lumen (not shown) of the catheter using the syringe with sufficient pressure that it flows distally through the lumen and is infused into surrounding body tissue through the infusion ports 28. The resultant bonding of the distal end of the localization wire 16 to the surrounding target tissue ensures with much greater certainty than the use of mechanical attachment means alone, such as the hook 26, that the localization wire will be properly positioned when the surgical procedure commences, thereby improving the likelihood that the proper target tissue will be excised with a minimum incision and resultant trauma to the patient.

Preferred bonding agents include any known effective biocompatible bonding materials, such as surgical adhesives, including cyanoacrylate, fibrin glue, and solvents.

An alternative to injection of the bonding agent through the lumen of the

medical instrument 10 is illustrated in Fig. 8. The bonding agent 33 may be stored in a rupturable container 34 which is disposed in the distal end of the medical instrument 10, adjacent to the infusion ports 28. When it is desired to release the bonding agent 33 through the infusion ports, a puncturing device 36
5 may be actuated by the practitioner to rupture the container 34. In the illustrated embodiment, the device 36 comprises a simple "spear" which is actuated distally to rupture the container, but it may alternatively comprise any suitable configuration for functioning equivalently. Additionally, it is within the scope of the invention to employ a chamber for containing the bonding agent which
10 includes a valved port, wherein the valve is actuated to an open position by the practitioner to release the bonding agent. Various other embodiments for accomplishing this function, as would be known to one of ordinary skill in the art, are deemed to fall within the scope of the invention as well.

Once the localization wire is securely bonded to the surrounding tissue,
15 the practitioner may withdraw the catheter and introducer needle assembly, leaving the localization wire in place to mark the target tissue for the ensuing surgical step in the biopsy or other medical procedure.

Figs. 4-7 illustrate a second "localization wire" embodiment, wherein like elements to those shown in the first embodiment are designated by like reference numerals, succeeded by the letter "a". This system may be styled as a "needle out" infusion system. In this embodiment, the catheter 12a comprises a dual lumen extrusion, including first and second lumens 38 and 40, respectively (Fig. 6a). The first lumen 38 accommodates the bonding agent, while the second lumen accommodates the localization wire. The catheter 12a further includes a
20 dual lumen proximal hub 42, which comprises a localization wire entry port 44 and a stopcock 32a.

In operation, the introducer needle 14 a is disposed coaxially outside of the catheter 12a, as illustrated in Fig. 4, and the instrument 10a is inserted into the patient's body in known fashion, under conventional imaging guidance. The
30 localization wire 16a is inserted distally through the port 44, either before or after

introduction of the instrument 10a into the patient's body. As in the first embodiment, once the instrument 10a is placed, the localization wire 16a is advanced distally until the indicator marks 25a indicate to the practitioner that the distal hook 26a is distal of the distal end of the catheter 12a and of the target lesion, as shown by the imaging equipment. The localization wires of Figs. 3 and 7 may be used interchangeably in either of the two disclosed embodiments, and are substantially identical except that the localization wire 16a includes filaments 46 near its distal end which provide additional surface area for bonding.

As in the previous embodiment, once the localization wire is in the proper position, bonding agent is injected into the catheter 12a, preferably using a syringe which is engaged with the stopcock 32a, so that the bonding agent flows distally through the first lumen 38 and is infused through the infusion ports 28a. Again, the infusion ports may be disposed about the catheter, in rows offset by 90 degrees with respect to one another, or otherwise staggered so that the bonding agent is evenly disposed about the catheter. Alternatively, as in the previous embodiment, the bonding agent may be stored in the distal end of the instrument 10a using an apparatus like that illustrated in Fig. 8. It is within the scope of this invention, as well, to store or inject two or more bonding agent compounds, comprising a reactant and a catalyst, at the injection site, and to mix the reactant and catalyst together at the appropriate time to catalyze a bonding agent.

Once the bonding agent has been injected, but before it has solidified, the catheter 12a and introducer needle 14a are withdrawn from the patient's body, leaving the localization wire in place.

Still a third embodiment, which functions in a manner equivalent to that of a localization wire, is illustrated in Figs. 9 and 10. In this embodiment, a catheter 48, which comprises a proximal hub 50, a distal end 52, and a lumen 54, is insertable into a patient's body using conventional image guidance techniques, so that the distal end 52 is disposed at a desired target tissue site. Once properly located, a bonding agent 33 is infused through one or more infusion ports 56 to surrounding target tissue, in order to bond the distal end of the catheter 48 to the

surrounding tissue. Again, as in the previous embodiments, the bonding agent may be injected into the lumen 54 of the catheter through the proximal hub 50, or may alternatively be stored in the distal end 52 of the catheter and selectively released at the desired time.

5 Figs. 11 and 12 illustrate two alternative embodiments for the outer tube 58 of the catheter in any of the foregoing embodiments. In Fig. 11, the tube 58 comprises a stainless steel braid, the proximal end 60 of which is encapsulated by a polymer, such as polyamide, and the distal end 62 of which is exposed. The exposed distal end is preferably approximately 1-2 centimeter (cm) in length,
10 though it may be longer or shorter if desired. In operation, interstices 64 between bands 66 of the exposed braided portion 62 function as openings for permitting infusion of bonding agent to surrounding tissue, instead of the infusion ports disclosed in the preceding embodiments. If the exposed braided portion is expanded, the interstices will be enlarged and will permit the flow of more
15 bonding agent therethrough.

 In a manner in some respects similar to the embodiment of Fig. 11, the Fig. 12 embodiment comprises an outer tube 58 having a sleeve 68 surrounding a coil 70 of suitable material. In the distal end of the tube 58, the coil 70 may be stretched to create interstices 72 between bands 74 of the coil. Bonding material
20 may be infused, as desired, outwardly through the interstices 72 of the expanded coil, and then through holes 76 in the sleeve 68 to surrounding tissue. Alternatively, the sleeve could be retracted to expose the coil, in which case the sleeve holes 76 would be unnecessary.

 Fig. 13 illustrates the distal end of a medical instrument 78 which is
25 shown and described in co-pending application Serial No. 09/057,303, commonly assigned with the present application and expressly incorporated by reference herein. The instrument 78 comprises a tissue acquisition or biopsy instrument and preferably includes a tip 80 having an electrosurgical element 82 for entering tissue, and a shaft 84, on which is disposed a radially extendable and retractable
30 cutting element or wire 86. The cutting element 86 is preferably energized by RF

energy provided by an electrosurgical generator.

In operation, the instrument 78 is moved axially to a position wherein the distal tip 80 is preferably distal to a target lesion or tissue to be removed, using a suitable imaging technique. In the prior art, such imaging techniques for biopsy procedures and the like typically include the use of a stereotactic or sonographic imaging system, both of which are relatively expensive and not always available in an average community hospital. This approach is designed to combine the imaging and cutting steps so that both occur simultaneously. For example, in the case of a breast biopsy procedure, the breast is clamped in order to effectively utilize the imaging equipment, after which the instrument is inserted into the breast under imaging guidance to the lesion location. Then, under continued imaging guidance, the cutting element is actuated and the target tissue removed.

However, an important advantage of the present invention is the ability to “uncouple” the imaging environment from the procedural environment in a typical surgical or biopsy procedure, and the resultant important ability to utilize unmodified mammography equipment, readily available in most hospitals, to position the distal end of the instrument during the imaging step, rather than expensive and specialized stereotactic equipment. Then, the procedural step may occur later, in another area of the hospital. In the case of breast biopsies, this “uncoupling” also permits the patient’s breast to be unclamped for the procedural step, resulting in increased patient comfort and easier working conditions for the practitioner.

These advantages are made possible because the inventive apparatus and technique permits the securement of the distal end of the instrument to the target tissue or lesion with sufficient confidence that the patient may be moved to the procedural environment without fear of having it slip away from the target tissue. This securement is accomplished using a fixation agent, which preferably comprises a bonding agent like that disclosed in connection with the foregoing localization wire and catheter embodiments. In a manner similar to those embodiments, once the instrument is positioned in a desired position, the bonding

agent is injected into a lumen of the instrument, or, alternatively, in a manner like that described supra, released from a container or chamber in the distal end of the instrument, so that it may be infused from one or more infusion ports 88 disposed on the distal end of the instrument. Preferably, the ports 88 are disposed on a
5 bushing or sleeve 90 which has a linear slot 92 for permitting passage of the cutting element 86 as it is extended and retracted radially, and which is rotatable relative to the shaft 84. Thus, when the bonding agent is infused to the surrounding tissue, so that the bushing 90 is affixed in place relative to the surrounding tissue, the cutting element 86 will still be rotatable on the underlying
10 shaft 84 in order to permit circumferential cutting of tissue, as desired, during the later procedural step. Suitable care is taken that only a sufficient amount of bonding agent is dispensed to bond the bushing to surrounding tissue, and not the shaft or tip of the instrument, in order that the shaft and tip continue to be rotatable relative to the bushing.

15 Of course, the bushing 90 may be constructed in number of alternative ways, as will be apparent to those of ordinary skill in the art. For example, as shown in Figs. 11 and 12, the bushing could be comprised of a braided or coil material, so that interstices between braids or coils thereof could function as the infusion openings.

20 Rather than using a bonding agent, a mechanical fixation agent may be utilized to secure the distal end of the instrument to surrounding tissue. For example, Fig. 14 illustrates an alternative embodiment to that of Fig. 13, wherein a mechanical fixation structure 94 is utilized to secure the distal end of the instrument to surrounding tissue, rather than a bonding agent. In this
25 embodiment, wherein like elements to those of Fig. 13 are designated by like reference numerals, succeeded by the letter "b", the mechanical fixation structure 94 comprises an expandable Mallicot structure, having a rotatable bushing 90b and a plurality of expandable bands 96. Actuating pushrods 98, of which there are preferably four, arranged circumferentially 90 degrees apart, are provided to
30 actuate the bands 96 between their expanded positions (as shown), in which they

are positioned to anchor the distal tip 80b to the desired tissue site, and their retracted positions.

Fig. 15 illustrates another modified embodiment which is similar to that of Fig. 14, and wherein like elements to those of Fig. 14 are designated by like reference numerals, succeeded by the letter "c". The only difference between this
5 embodiment and the Fig. 14 embodiment is that the bands 96c are split at their centers, to form protruding portions 100, for the purpose of permitting further radial extension of each band and to also permit the protruding portions 100 to attach themselves to adjacent tissue.

10 Figs. 16 and 17 schematically illustrate still another modified mechanical fixation structure 94d, comprising a linkage, which may be substituted for the structures 94 and 94c of Figs. 14 and 15, respectively, wherein Fig. 16 illustrates the linkage in its retracted configuration and Fig. 17 illustrates it in its radially expanded configuration.

15 Fig. 18 schematically illustrates yet another modified mechanical fixation structure 94e, comprised of a plurality of radially retractable and extendable wires 102.

Fig. 19 schematically illustrates still another modified mechanical fixation structure 94f, of the bone anchor type, comprised of a nitinol tube 104 and
20 radially expandable flaps 106.

In Fig. 20, there is shown another modified mechanical fixation structure 94g, comprised of a rolled stent which may be unrolled to expand radially and provide an anchoring function by axially retracting a sleeve 108.

Fig. 21 shows still another modified mechanical fixation structure 94h
25 comprised of a plurality of extendable wires 110.

Fig. 22 illustrates a modified mechanical fixation structure 94i which comprises a radially expandable and retractable basket.

Any of the foregoing mechanical fixation structures may be interchangeably employed in the embodiments of Figs. 14 and 15, and it is within
30 the scope of this invention to also employ other mechanical fixation structures

which are known conventionally for anchoring medical devices in the body.

Still another means for bonding the distal end of the instrument 78 to surrounding tissue, which is within the scope of the present invention, is to apply RF energy to the tissue, using an electrosurgical coagulation element. The
5 electrosurgical coagulation element may comprise one of the existing electrosurgical elements 82 or 86, or preferably another coagulation element 112 (Fig. 13) which may be disposed on or near the bushing 90. Activation of the coagulation element 112 for a short interval coagulates the tissue surrounding the tissue, thereby bonding the bushing to the tissue. Alternatively, the element 112
10 could comprise a heating rod for cauterizing tissue, similar to the function of a branding iron, to produce the same type of bonding effect by "sticking" the cauterized tissue to the distal end of the instrument.

This approach may also be utilized in the localization wire embodiments illustrated in Figs. 1-12, by employing an electrosurgical coagulation element on
15 the distal end thereof, which is connected to a suitable electrosurgical generator, or, alternatively, by employing an electrical heating element for cauterizing tissue.

While this invention has been described with respect to various specific examples and embodiments, it is to be understood that the invention is not
20 limited thereto and that it can be variously practiced within the scope of the following claims.

What is Claimed is:

1. A medical device comprising a tube having a distal end, a proximal end, and a longitudinal axis, the device being adapted for placement of said distal end into a patient's body at a desired location, said medical device having a fixation agent disposed on said distal end, the fixation agent being
5 adapted for affixing the distal end of said medical device at said desired location.
2. The medical device as recited in Claim 1, wherein said device comprises a localization wire.
3. The medical device as recited in Claim 1, wherein said fixation agent comprises a bonding agent, and said device further comprising at least one opening for dispensing said bonding agent into the patient's body.
4. The medical device as recited in Claim 3, wherein said bonding agent comprises a surgical adhesive.
5. The medical device as recited in Claim 4, wherein said surgical adhesive comprises a cyanoacrylate.
6. The medical device as recited in Claim 3, wherein said bonding agent comprises a fibrin glue.
7. The medical device as recited in Claim 3, wherein said bonding agent comprises a solvent.
8. The medical device as recited in Claim 2, wherein said medical device comprises a catheter, the catheter having a lumen through which said localization wire is introduced into the patient's body.

9. The medical device as recited in Claim 8, wherein said fixation agent comprises a bonding agent, and said catheter has a second lumen which accommodates said bonding agent.

10. The medical device as recited in Claim 3, wherein said tube comprises a braided outer wall, the braided outer wall having an interstice which comprises said at least one opening for dispensing said bonding agent.

11. The medical device as recited in Claim 3, wherein said tube comprises an outer wall formed from a coil of material, said coil being utilized to create an interstice which comprises said at least one opening for dispensing said bonding agent.

12. The medical device as recited in Claim 3, wherein said medical device comprises a surgical instrument.

13. The medical device as recited in Claim 12, wherein said surgical instrument comprises a tissue acquisition device having a longitudinal axis about which said device is rotatable and comprises:

5 a cutting element disposed on said tube for cutting surrounding tissue; and
a bushing disposed on said tube which is rotatable relative to said tube;
wherein the bonding agent dispensed through said at least one opening affixes said bushing to surrounding tissue, so that the instrument is secured in a desired location without preventing rotational movement thereof.

14. The medical device as recited in Claim 1, wherein said fixation agent comprises a mechanical fixation agent, which is actuatable to extend outwardly into tissue surrounding the distal end of said device to engage said tissue and to thereby anchor the distal end of the device at said desired location.

15. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a Mallicot structure.

16. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a hinged linkage.

17. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a plurality of radially extendable and retractable wires.

18. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a tube and a plurality of radially expandable flaps extending from said tube.

19. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a rolled stent and an axially movable sleeve, wherein when said sleeve is moved proximally the stent is exposed and unrolls to engage surrounding tissue and affix the distal end of the medical device.

20. The medical device as recited in Claim 14, wherein said mechanical fixation agent comprises a radially expandable and retractable basket.

21. The medical device as recited in Claim 1, wherein said fixation agent comprises an electrosurgical element disposed on the tube distal end, which coagulates tissue surrounding the tube distal end and thereby causes said tissue to be affixed to the tube distal end.

22. The medical device as recited in Claim 1, wherein said fixation agent comprises an electrical heating element disposed on the tube distal end, which cauterizes tissue surrounding the tube distal end and thereby causes said

tissue to be affixed to the tube distal end.

23. A tissue acquisition instrument for retrieving body tissue, having a longitudinal axis and comprising:

a distal end adapted for entry into a patient's body;

5 a cutting element disposed on said instrument for cutting surrounding tissue; and

structure disposed on said distal end for securing said tissue acquisition instrument at a predetermined desired location, in order to ensure that the tissue acquisition instrument remains in place during a tissue acquisition procedure so that desired tissue is properly acquired.

24. The tissue acquisition instrument as recited in Claim 23, wherein said structure comprises a lumen containing a bonding agent and at least one opening disposed at said distal end for dispensing said bonding agent to surrounding tissue.

25. The tissue acquisition instrument as recited in Claim 24, wherein said instrument is rotatable about said longitudinal axis, said instrument further comprising:

5 a bushing disposed on said instrument which is rotatable relative to said instrument;

wherein the bonding agent dispensed through said at least one opening affixes said bushing to said surrounding tissue, so that the instrument is secured in a desired location without preventing rotational movement thereof.

26. The tissue acquisition instrument as recited in Claim 24, wherein said bonding agent comprises a surgical adhesive.

27. The tissue acquisition instrument as recited in Claim 26, wherein

said surgical adhesive comprises a cyanoacrylate.

28. The tissue acquisition instrument as recited in Claim 24, wherein said bonding agent comprises a fibrin glue.

29. The tissue acquisition as recited in Claim 24, wherein said bonding agent comprises a solvent.

30. The tissue acquisition instrument as recited in Claim 23, wherein said structure comprises mechanical attachment structure extendable outwardly into said surrounding tissue.

31. The tissue acquisition instrument as recited in Claim 30, wherein said mechanical fixation agent comprises a Mallicot structure.

32. The tissue acquisition instrument as recited in Claim 31, wherein said mechanical fixation agent comprises a hinged linkage.

33. The tissue acquisition instrument as recited in Claim 31, wherein said mechanical fixation agent comprises a plurality of radially extendable and retractable wires.

34. The tissue acquisition instrument as recited in Claim 31, wherein said mechanical fixation agent comprises a tube and a plurality of radially expandable flaps extending from said tube.

35. The tissue acquisition instrument as recited in Claim 31, wherein said mechanical fixation agent comprises a rolled stent and an axially movable sleeve, wherein when said sleeve is moved proximally the stent is exposed and unrolls to engage said surrounding tissue and affix the distal end of the medical

device.

36. The tissue acquisition instrument as recited in Claim 31, wherein said mechanical fixation agent comprises a radially expandable and retractable basket.

37. The tissue acquisition instrument as recited in Claim 23, wherein said instrument comprises a biopsy instrument.

38. The tissue acquisition instrument as recited in Claim 23, wherein said structure comprises an electrosurgical cutting element.

39. The tissue acquisition instrument as recited in Claim 23, wherein said instrument is rotatable about said longitudinal axis, said instrument further comprising:

5 a bushing disposed on said instrument which is rotatable relative to said instrument;

wherein said structure comprises an electrosurgical element disposed on said bushing, wherein when said electrosurgical element is energized, the surrounding tissue is coagulated and bonds to said bushing, so that the instrument is secured in a desired location without preventing rotational movement thereof.

10

40. The tissue acquisition instrument as recited in Claim 24, wherein said instrument is rotatable about said longitudinal axis, said instrument further comprising:

15 a bushing disposed on said instrument which is rotatable relative to said instrument;

wherein said structure comprises an electrical heating element disposed on said bushing, wherein when said electrical heating element is energized, the surrounding tissue is cauterized and bonds to said bushing, so that the instrument

is secured in a desired location without preventing rotational movement thereof.

41. A method of performing a medical procedure using a medical device comprising a tube having a distal end, a proximal end, and a longitudinal axis, the method comprising the steps of:

- a) placing the distal end of the tube in a patient's body, so that the
5 distal end is disposed in a desired tissue location; and
- b) dispensing a bonding agent from said tube into tissue surrounding said distal end, so that the distal end of the tube becomes affixed to said desired tissue location.

42. A method for performing a tissue acquisition procedure using a tissue acquisition instrument having a distal end, a proximal end, a longitudinal axis, and a cutting element, the method comprising the steps of:

- a) placing the distal end of the instrument in a patient's body, so that
5 the distal end is disposed in a desired tissue location;
- b) affixing the distal end of the instrument to said desired tissue location, so that the instrument does not move relative to the desired tissue location during the tissue acquisition procedure; and
- c) actuating the cutting element to acquire one or more tissue
10 samples.

43. The method as recited in Claim 42, wherein the step of affixing the distal end of the instrument is performed by dispensing a bonding agent from said distal end into surrounding tissue.




44. The method as recited in Claim 42, wherein the step of affixing the distal end of the instrument is performed by actuating a mechanical element to extend from said distal end and attach itself to surrounding tissue.

45. The method as recited in Claim 42, wherein the step of affixing the distal end of the instrument is performed by activating an electrosurgical element and operating it to coagulate tissue surrounding the distal end of the instrument, to an extent that the tissue bonds to the instrument distal end.

46. The method as recited in Claim 42, wherein the step of affixing the distal end of the instrument is performed by activating an electrical heating element and operating it to cauterize tissue surrounding the distal end of the instrument, to an extent that the tissue bonds to the instrument distal end.

47. The method as recited in Claim 42, wherein the tissue acquisition procedure is a biopsy procedure.

48. The method as recited in Claim 42, wherein the patient is transported from one location to another between steps b) and c).






Fig. 3a




Fig. 3b














Fig. 3c



















Fig. 13













Fig. 22





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 10/00, 17/00		A3	(11) International Publication Number: WO 00/12009
			(43) International Publication Date: 9 March 2000 (09.03.00)
(21) International Application Number: PCT/US99/19123 (22) International Filing Date: 24 August 1999 (24.08.99) (30) Priority Data: 09/146,185 1 September 1998 (01.09.98) US (71) Applicant: SENORX, INC. [US/US]; Suite 144, 13766 Alton Parkway, Irvine, CA 92618 (US). (72) Inventors: BURBANK, Fred, H.; 30982 Steeplechase Drive, San Juan Capistrano, CA 92675 (US). LUBOCK, Paul; 30 Bethany, Laguna Niguel, CA 92677 (US). JONES, Michael, L.; 34441 Camino el Molino, Capistrano Beach, CA 92624 (US). QUICK, Richard, L.; 32181 Fall River Road, Trabuco Canyon, CA 92679 (US). (74) Agent: STOUT, Donald, E.; Stout, Uxa, Buyan & Mullins, LLP, 4 Venture #300, Irvine, CA 92618 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. (88) Date of publication of the international search report: 29 June 2000 (29.06.00)	
(54) Title: SECURING SURGICAL INSTRUMENTS AT TARGET TISSUE SITES 			
(57) Abstract Devices and methods are provided for securely affixing a medical instrument to desired tissue in a patient's body, using a fixation agent. Such medical instruments may comprise localization wires or tissue acquisition instruments, such as biopsy instruments, for example. In the case of tissue acquisition instruments, the inventors have discovered significant advantages for securely affixing the distal end of the tissue acquisition instrument to a particular tissue target area. For example, such an approach permits the imaging environment to be uncoupled from the procedural environment so that expensive and often unavailable imaging equipment, such as stereotactic imaging equipment, need not be used. In a preferred embodiment, a bonding agent, such as adhesive, surgical glue, or a solvent, is used as the fixation agent.			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LJ	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/19123

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B10/00 A61B17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 03843 A (UNIVERSITY OF CALIFORNIA) 9 February 1995 (1995-02-09) page 12, line 12; figures 5,8 page 13, paragraph 2 - paragraph 3 ---	1,2,8,9
X	EP 0 601 709 A (VANCE) 15 June 1994 (1994-06-15) figure 1 ---	1,23
A	US 5 749 887 A (HESKE) 12 May 1998 (1998-05-12) figures 1,2A ---	1,2,14
A	US 5 158 084 A (GHIATAS) 27 October 1992 (1992-10-27) ---	
A	US 4 425 908 A (SIMON) 17 January 1984 (1984-01-17) ---	
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

29 March 2000

Date of mailing of the international search report

12.04.2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Barton, S

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/19123

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 98 24372 A (ANGIOTRAX) 11 June 1998 (1998-06-11) figures 3,4,6,8	1,14,17, 20 23,30, 33,36
X	US 4 966 583 A (DEBBAS) 30 October 1990 (1990-10-30) figures 4,5	1,14,23, 30
X A	US 5 755 697 A (JONES) 26 May 1998 (1998-05-26) figures 9,10,15,16	1,14-16 31-33
X A	WO 94 27670 A (CARDIAC PATHWAYS) 8 December 1994 (1994-12-08) figures 3,4	1,14,17 33
X A	US 5 653 718 A (YOON) 5 August 1997 (1997-08-05) figures 45-49	1,18 34
A	US 5 700 273 A (BUELNA) 23 December 1997 (1997-12-23) column 5, line 30 - line 38; figures 2,4	15,31
A	US 5 449 382 A (DAYTON) 12 September 1995 (1995-09-12) abstract; claim 6	19,35
A	EP 0 797 957 A (ECLIPSE) 1 October 1997 (1997-10-01) figures 5,6	15-17,20
A	EP 0 769 281 A (USSC) 23 April 1997 (1997-04-23) column 13, last paragraph; figures 31-33	23, 30-32,35
A	US 5 766 163 A (MUELLER) 16 June 1998 (1998-06-16)	

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 99/19123

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 41-48
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☒ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
1,2,8,9,14-20,23,30-36
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1,2,8,9,23

Medical device with tissue attachment and localisation wire

2. Claims: 1,3-13,23-29,40

Medical device with [means for dispensing] a dispensable bonding agent as means for fixing distal end to target tissue

3. Claims: 1,14-20,23,30-36

Medical device with expandable mechanical structure as means for fixing the distal end to target tissue

4. Claims: 1,21,22,38,39

Medical device with electrocautery means as means for fixing the distal end to target tissue

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/19123

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9503843 A	09-02-1995	AU 7404994 A US 5921982 A	28-02-1995 13-07-1999
EP 601709 A	15-06-1994	AU 5050593 A CA 2102084 A JP 6197904 A US 5488958 A	19-05-1994 10-05-1994 19-07-1994 06-02-1996
US 5749887 A	12-05-1998	DE 4424394 A	18-01-1996
US 5158084 A	27-10-1992	NONE	
US 4425908 A	17-01-1984	NONE	
WO 9824372 A	11-06-1998	US 5910150 A US 5941893 A AU 5366498 A AU 5510198 A US 5951581 A WO 9824373 A US 5931848 A US 5899915 A US 6010476 A	08-06-1999 24-08-1999 29-06-1998 29-06-1998 14-09-1999 11-06-1998 03-08-1999 04-05-1999 04-01-2000
US 4966583 A	30-10-1990	CA 2080897 A EP 0591140 A EP 0699088 A WO 9116099 A WO 9311827 A US 5445645 A US 5662674 A US 5183463 A US 5301682 A	27-10-1991 13-04-1994 06-03-1996 31-10-1991 24-06-1993 29-08-1995 02-09-1997 02-02-1993 12-04-1994
US 5755697 A	26-05-1998	NONE	
WO 9427670 A	08-12-1994	US 5507802 A	16-04-1996
US 5653718 A	05-08-1997	US 5540648 A	30-07-1996
US 5700273 A	23-12-1997	AU 6343796 A CA 2205176 A EP 0785752 A WO 9703613 A US 5846253 A US 5836955 A US 5836956 A	18-02-1997 06-02-1997 30-07-1997 06-02-1997 08-12-1998 17-11-1998 17-11-1998
US 5449382 A	12-09-1995	US 5578075 A	26-11-1996
EP 797957 A	01-10-1997	US 5725521 A AU 1660097 A CA 2200916 A JP 10033550 A	10-03-1998 02-10-1997 29-09-1997 10-02-1998
EP 769281 A	23-04-1997	CA 2187975 A US 5879357 A	21-04-1997 09-03-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/19123

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5766163 A	16-06-1998	NONE	